











	Model	OREANE LV PRO 500	
	Code Production	917480	
	Interface :		
	Overall Dimension (Width-Depth-Height) *open mm Packaging Dimension (WxDxH) mm Gross weight Kg Net weight Kg Volume mc		600x600(885*)x720 690x670x870 61 55 0,45
	Rack size mm Max door /hood opening mm Max glasses/plate Height mm General construction Door/hood Construction		500x500 285 255 double skin double skin
	Tank construction Tank volume liter Tank heating element W Tank surface strainers		deep drawn 15 2100 composite
	Wash pump type Wash pump power W Wash temperature °C		double flow 470 60
	Boiler type Boiler volume liter Back-flow system Boiler heating element W		without pressure 6 break tank 4900
	Rinse booster pump Rinse booster pump power W Rinse temperature °C Rinse water consumption Liter /rack Optimal external water pressure bar		YES 200 65 (80) 2,2 2 - 4
	Drain system Drain pump		deep drain standard built in
	Rinse aid dispenser Detergent dispenser		peristaltic peristaltic YES YES
	Wash cycle sec		60 - 120 -150
	Electric Power W Electric Connection V - ph - Hz Fuse A		5400 400V 3N 50Hz 16
	Water softner type continuous		YES
	Plates racks n°1		780072

▶	Flat Rack	n°1	780135
	Support for saucers	n°-	NO
	Cutterly Rack	n°1	780139
	Electric cable	n°1	YES
	Drain hose	n°1	YES
	Fill hose	n°1	YES

